




Lamp Type	Part Number	Watts	Volts	Beam Spread	Base	Lumens/ CBCP	Color Temp	Rated Life (Hours)
	<b>LED MR8</b> LA-LED-MR8-3W-2700	3	12	80°	G4 Bi-Pin	120	2700	40,000
	LA-LED-MR8-3W-3000	3	12	80°	G4 Bi-Pin	120	3000	40,000
	<b>LED MR11</b> LA-LED-MR11-3W-2700	3	12	40°	G4 Bi-Pin	180	2700	40,000
	LA-LED-MR11-3W-3000	3	12	40°	G4 Bi-Pin	180	3000	40,000
	<b>LED MR16</b> LA-LED-MR16-4W-2700-15	4	12	15°	GU5.3 Bi-Pin	240	2700	40,000
	LA-LED-MR16-4W-2700-30	4	12	30°	GU5.3 Bi-Pin	240	2700	40,000
	LA-LED-MR16-4W-2700-45	4	12	45°	GU5.3 Bi-Pin	240	2700	40,000
	LA-LED-MR16-4W-2700-60	4	12	60°	GU5.3 Bi-Pin	240	2700	40,000
	LA-LED-MR16-4W-2700-100	4	12	100°	GU5.3 Bi-Pin	240	2700	40,000
	LA-LED-MR16-4W-3000-15	4	12	15°	GU5.3 Bi-Pin	260	3000	40,000
	LA-LED-MR16-4W-3000-30	4	12	30°	GU5.3 Bi-Pin	260	3000	40,000
	LA-LED-MR16-4W-3000-45	4	12	45°	GU5.3 Bi-Pin	260	3000	40,000
	LA-LED-MR16-4W-3000-60	4	12	60°	GU5.3 Bi-Pin	260	3000	40,000
	LA-LED-MR16-4W-3000-100	4	12	100°	GU5.3 Bi-Pin	260	3000	40,000
	LA-LED-MR16-4W-5000-45	4	12	45°	GU5.3 Bi-Pin	320	5000	40,000
	LA-LED-MR16-4W-5000-60	4	12	60°	GU5.3 Bi-Pin	320	5000	40,000
	LA-LED-MR16-5W-2700-100	5	12	100°	GU5.3 Bi-Pin	340	2700	40,000
	LA-LED-MR16-5W-3000-100	5	12	100°	GU5.3 Bi-Pin	360	3000	40,000
	LA-LED-MR16-6W-2700-15	6	12	15°	GU5.3 Bi-Pin	450	2700	40,000
	LA-LED-MR16-6W-2700-30	6	12	30°	GU5.3 Bi-Pin	450	2700	40,000
	LA-LED-MR16-6W-2700-45	6	12	45°	GU5.3 Bi-Pin	450	2700	40,000
	LA-LED-MR16-6W-2700-60	6	12	60°	GU5.3 Bi-Pin	450	2700	40,000
	LA-LED-MR16-6W-3000-15	6	12	15°	GU5.3 Bi-Pin	470	3000	40,000
	LA-LED-MR16-6W-3000-30	6	12	30°	GU5.3 Bi-Pin	470	3000	40,000
	LA-LED-MR16-6W-3000-45	6	12	45°	GU5.3 Bi-Pin	470	3000	40,000
	LA-LED-MR16-6W-3000-60	6	12	60°	GU5.3 Bi-Pin	470	3000	40,000
	LA-LED-MR16-6W-5000-45	6	12	45°	GU5.3 Bi-Pin	510	5000	40,000
	LA-LED-MR16-6W-5000-60	6	12	60°	GU5.3 Bi-Pin	510	5000	40,000
	LA-LED-MR16-9W-2700-30	9	12	30°	GU5.3 Bi-Pin	560	2700	40,000
	LA-LED-MR16-9W-2700-45	9	12	45°	GU5.3 Bi-Pin	560	2700	40,000
	LA-LED-MR16-9W-2700-60	9	12	60°	GU5.3 Bi-Pin	560	2700	40,000
	LA-LED-MR16-9W-3000-30	9	12	30°	GU5.3 Bi-Pin	580	3000	40,000
LA-LED-MR16-9W-3000-45	9	12	45°	GU5.3 Bi-Pin	580	3000	40,000	
LA-LED-MR16-9W-3000-60	9	12	60°	GU5.3 Bi-Pin	580	3000	40,000	
<b>Bluetooth</b>	LA-LED-MR16-6W-RGB-45	10	12	45°	GU5.3 Bi-Pin	Vary	Vary	40,000